

TOS MST TABRIZ
VERTICAL DRILLING MACHINE
MS-32 B



STANDART ACCESSORIES

Hive 4 x 3
Hive 4 x 2
Adaptor 4 x 18
Adaptor 2 x 18
Coolant System
LED Working Light
Tool Bag

SPECIFICATIONS

Tapping System
Spindle Auto Feeding System
Up-Down Travel Top Body
Emergency Stop With Auto Brake



HAKSAN TAKIM TEZGAHLARI MAKİNA SAN. ve TİC.LTD.ŞTİ.

Abdi İpekçi Caddesi 1. Emintaş Sanayi Sitesi No:74/121 Bayrampaşa / İSTANBUL

Tel : 0212 613 02 09 pbx - Faks : 0212 576 44 20

info@haksanmakina.com.tr

www.haksanmakina.com.tr

TOS TABRIZ VERTICAL DRILLING MACHINE

TEKNİK BİLGİLER	Birim	MS-32 B
Max. Drilling Capacity	mm	32
Max. tapping Capacity	Metric	M-30
Max. Spindle Travel	mm	200
Distance Between Spindle Center to Column	mm	305
Distance Between Spindle to Table	mm	625
Distance Between Spindle to Foot Table	mm	1150
Top Body Travel	mm	350
Spindle Taper	MT	4
Number of Spindle Speed	Step	15
Speed of Spindle	Rpm	56 - 2240
Number of Spindle Auto Feed	Step	4
Speed of Spindle Auto Feed	Mm/rev	0.11 - 0.45
Table Working Surface – Horizontal (L x D)	mm	400 x 316
Table Working Surface – Vertical (L x D)	mm	510 x 205
Foot Table Working Surface (L x D)	mm	420 x 415
Column Diameter	mm	Ø 140
Motor Power	kW	2,2
Machine Size – L x D x H	mm	550 x 1100 x 2110
Net / Brüt Weight	kgs	645 / 680

HAKSAN TAKIM TEZGAHLARI MAKİNA SAN. ve TİC.LTD.ŞTİ.

Abdi İpekçi Caddesi 1. Emintaş Sanayi Sitesi No:74/121 Bayrampaşa / İSTANBUL

Tel : 0212 613 02 09 pbx - Faks : 0212 576 44 20

info@haksanmakina.com.tr
www.haksanmakina.com.tr